


产品特点 Product Features

- 电池内部无游离酸，气体复合效率高，使用安全性高。
- 特殊板栅合金，合适的电解液比重，充分保证寿命。
- 极板采用双面涂膏技术，确保电池性能一致优越。
- 特别设计的高功率型电池（适合IDC机房等大电流放电场合）。
- 前置端子设计（方便安装、维护，节约安装空间）。
- No free acid inside battery, high efficient gas recombination, high operation safety.
- Special alloy of grid, adequate specific gravity of electrolyte secures the battery life.
- Two-sided plating technology, more advantage battery function.
- Special designed high power battery (applicable for high discharge current sites such as IDC room).
- Front top terminal (easy to install, maintain and save space).



外形尺寸 Dimension (mm)




电池特征 Battery Characteristics

标称电压 (V) Nominal Voltage		12
容量 Capacity (25°C)	20小时率	160Ah
	10小时率	150Ah
	5小时率	128Ah
	1小时率	82.5Ah
近似外形尺寸 Approd.Dimension	长 L (mm)	538
	宽 W (mm)	208
	高 H (mm)	212
	总高 OH (mm)	212
不同环境温度下的放置期限 Storage period at various temperature	25°C以下	6个月
	30°C以下	4个月
	35°C以下	3个月
	40°C以下	2个月
运行温度 Operating Temp Range	放电 Discharge	-15°C ~ 50°C
	※充电 Charge	-15°C ~ 45°C
	存储 Storage	-15°C ~ 50°C
推荐温度 Nominal OperatingTemp Range		25°C
※当温度偏离25°C时,要用温度补偿后的电压充电 If the temperature variesy from 25°C, Charge with voltage after temperature compensation		
重量 Weight		约48kg
端子 Terminal		铜芯(M8)
池壳材料 Container material		ABS 阻燃等级:UL 94-HB/V-0
内阻 (完全充电) IR, fully charged (25°C)		约2.8mΩ
浮充使用期充电方法 Charging method for floating use (25°C)		定电压13.65V 限流15.0~37.5A
设计浮充寿命 Designed floating life		6年(25°C)

电池限流恒压充电特性

Charge Characteristics Constant Voltage with Current Limit



放电电流和终止电压的关系

Relationship of Discharge Current to Final Discharge Voltage

放电电流 Discharge current	放电允许最低终止电压 Lowest Discharge Final Voltage Allowed
0.2CA未滿	1.75V/单格
0.2CA以上 0.5CA未滿	1.70V/单格
0.5CA以上 1.0CA未滿	1.55V/单格
1.0CA以上	1.30V/单格

定功率放电表 Constant Wattage Discharge Characteristics (25℃ 瓦特/单格watts/Cell)

终止电压	5 min	10 min	15 min	20 min	25 min	30 min	40 min	45 min	1h	1.5h	2h	3h	4h	5h	8h	10h
1.65V	763	586	465	378	328	290	249	212	179.0	136.8	109.5	79.6	63.4	54.4	36.2	29.5
1.67V	755	573	460	375	326	288	248	211	178.0	135.6	109.0	79.1	63.1	54.0	36.1	29.4
1.70V	719	560	455	373	324	285	247	210	177.0	134.4	108.3	78.6	62.7	53.7	36.0	29.3
1.75V	665	534	435	365	320	283	238	209	174.0	132.0	107.8	78.1	62.4	53.4	35.9	29.2
1.80V	619	480	407	345	312	281	230	207	172.0	128.9	107.0	76.7	62.1	53.0	35.8	29.0

充电注意 Charging Recommendations

当温度偏离25℃时，请按每变化1℃，浮充使用按-3mV/单格进行修正，均充按-4mV/单格进行修正。
If the operating temperature varies significantly from the center value (25℃), temperature compensation for the charging voltage is recommended. The recommendation is -3mV/℃/cell for float use, and -4mV/℃/cell for cyclic use.



杰士汤浅株式会社 GS YUASA CORPORATION
广东汤浅蓄电池有限公司
地址: 广东省佛山市顺德区大良

认证标识 Approval indication



ISO 9001
Quality Management Systems
CERTIFIED



ISO 14001
Environmental Management
CERTIFIED



ISO 45001
Occupational Health And Safety Management
CERTIFIED



FM 45770 EMS 99952 OHS 750241